# SOBIL PREMIUM PLUS 4T 20W-40

#### **DESCRIPTION:**

**Sobi**l<sup>™</sup>

LUBRICANTS

**SOBIL PREMIUM PLUS 4T 20W-40** is high performance, synthetic technology 4-stroke motorcycle engine oil specially developed for new generation motorcycles. It is formulated with premium quality base stocks and cutting-edge technology of high performance additive system which provides excellent performance and optimum power output.

**SOBIL PREMIUM PLUS 4T 20W-40** offers powerful protection to engine and its components from friction and wear, smooth clutch operation, superior engine cleanliness, reduces the heat of engine even at elevated temperatures.

#### **APPLICATION:**

**SOBIL PREMIUM PLUS 4T 20W-40** is recommended for 4-stroke motorcycles of all leading OEM's recommending SAE 20W-40 grade engine oil.

#### **SPECIFICATIONS:**

SOBIL PREMIUM PLUS 4T 20W-40 meets & exceeds the requirements and performance specifications of:

- > API SN
- JASO Ma2

# **ADVANTAGES:**

**SOBIL PREMIUM PLUS 4T 20W-40** offer the following advantages:

- BS-VI compatible.
- Longer Engine Life.
- Smooth clutch operation.
- Keeps the engine cool & clean.
- Reduces engine noise & vibrations.
- Superior protection from friction, wear & rust.
- Maintains health of engine, gear & clutch.
- Catalyst compatible.

# **Guru Ram Lubricants**

Kh. No. 853,874,0, Village-Dulna, Abhanpur Raipur, Chattisgarh, India. 493885 Email : gururamlubricants1042018@gmail.com Website : www.patanjalilubricants.com Mobile Number : 9302700423, 9826186101



SOBIL PREMIUM PLUS 4T 20W-40

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	D 1500	L2.5
Density @ 29.5 C, gm/cc	D 4052	0.8600
Kinematic Viscosity @ 40 C, cSt	D 445	114
Kinematic Viscoity @ 100 C, cSt	D 445	14.44
Viscosity Index	D 2270	129
Total Base Number, mg KOH / gm	D 2896	6.66
Flash Point, C	D 92	242
Pour Point, C	D 97	-24

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

### **STORAGE**

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

# **ENVORNMENT, HEALTH AND SAFTEY**

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 25th Oct.2021

## **Guru Ram Lubricants**

Kh. No. 853,874,0, Village-Dulna, Abhanpur Raipur, Chattisgarh, India. 493885 Email : gururamlubricants1042018@gmail.com Website : www.patanjalilubricants.com Mobile Number : 9302700423, 9826186101

