

DESCRIPTION:

SOBIL MÈRE CARGO 15W-40 is high quality multi grade engine oil ideally made for medium and light duty cargo vehicles which are operated in severe city conditions with frequent start-stop operations.

APPLICATION:

SOBIL MÈRE CARGO 15W-40 Engine Oil recommended for high performance engines of all major cargo & mini-transport vehicles manufactured by Piaggio, TATA, Bajaj and Mahindra & Mahindra and others.

SPECIFICATIONS:

SOBIL MÈRE CARGO 15W-40 meets the specification requirements of:

- API CF-4/ CE/SG

ADVANTAGES:

SOBIL MÈRE CARGO 15W-40 offers the following advantages:

- Provides smooth ride to the cargo vehicles for start-stop operations.
- Excellent Load carrying capacity.
- Anti-wear, anti-oxidant and detergency properties.
- Minimizes sludge formation.
- Improves engine efficiency and reduce the deposits.
- Provides complete engine protection across different engine speeds & conditions.


Guru Ram Lubricants

Kh. No. 853,874,0, Village-Dulna, Abhanpur Raipur,
Chattisgarh, India. 493885

Email : gururamlubricants1042018@gmail.com

Website : www.patanjalilubricants.com

Mobile Number : 9302700423, 9826186101



PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Bright & Clear
Colour ASTM	D1500	L3.5
Density @29.5°C, gm/cc	D4052	0.8721
Kin. Viscosity @ 40°C, cSt	D445	108.7
Kin. Viscosity @ 100°C, cSt	D445	14.29
Viscosity Index	D2270	134
Flash Point, °C	D92	238
Pour Point, °C	D97	-27
Total Base Number, mg KOH/gm	D2896	6.35
CCS Viscosity @ -20°C, cP	D5293	6160

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

STORAGE:

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVORNMENT, HEALTH AND SAFTEY:

- ◆ Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point.
- ◆ This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- ◆ Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 26th Mar. 2022

Guru Ram Lubricants

Kh. No. 853,874,0, Village-Dulna, Abhanpur Raipur,
Chattisgarh, India. 493885
Email : gururamlubricants1042018@gmail.com
Website : www.patanjalilubricants.com
Mobile Number : 9302700423, 9826186101

