

SOBIL MÈRE TRACK XL 20W-50

DESCRIPTION:

SOBIL MÈRE TRACK XL 20W-50 is a premium high performance engine oil especially formulated for new generation four stroke engines. It is fortified with high level of detergent & dispersant additives and Viscosity Modifier which provides maximum protection for the engines.

APPLICATION:

SOBIL MÈRE TRACK XL 20W-50 is suitable for lubrication of four-stroke cars/SUV engines under moderate to severe operating conditions.

SPECIFICATIONS:

SOBIL MÈRE TRACK XL 20W-50 exceeds requirements of the following performance specifications:

API SL

CHARACTERISTICS:

SOBIL MÈRE TRACK XL 20W-50 having the outstanding features of:

- Excellent control on Engine wear and deposits.
- The high TBN effectively neutralizes the acids of combustion and prevents acid attack.
- Increased oil drain interval due to good thermal resistance.
- Retention of viscosity over vide temperature ranges.

Guru Ram Lubricants

Kh. No. 853,874,0, Village-Dulna, Abhanpur Raipur, Chattisgarh, India. 493885 Email : gururamlubricants1042018@gmail.com Website : www.patanjalilubricants.com Mobile Number : 9302700423, 9826186101

Sobil[®] LUBRICANTS

TECHNICAL SPECIFICATIONS: SOBIL MÈRE TRACK XL 20W-50

| PROPERTIES | ASTM TEST METHOD | TYPICAL VALUES |
|------------------------------|------------------|----------------|
| Appearance | Visual | Bright & Clear |
| Colour ASTM | Visual | Red |
| Density @29.5°C, gm/cc | D4052 | 0.8870 |
| Kin. Viscosity @ 40°C, cSt | D445 | 165.30 |
| Kin. Viscosity @ 100°C, cSt | D445 | 17.80 |
| Viscosity Index | D2270 | 118 |
| Flash Point, °C | D92 | 240 |
| Pour Point, °C | D97 | -21 |
| Total Base Number, mg KOH/gm | D2896 | 7.50 |
| CCS Viscosity @ -15°C, cP | D5293 | 6800 |

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

STORAGE:

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVORNMENT, HEALTH AND SAFTEY:

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point.
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 26th Mar. 2022

Guru Ram Lubricants

Kh. No. 853,874,0, Village-Dulna, Abhanpur Raipur, Chattisgarh, India. 493885 Email : gururamlubricants1042018@gmail.com Website : www.patanjalilubricants.com Mobile Number : 9302700423, 9826186101

