

SOBIL QUEN VQ

DESCRIPTION:

SOBIL QUEN VQ is specially formulated Vacuum Quenching Oil blended from selective hydro treated base oils and modern & effective anti-oxidation, wetting and anti-foam additives.

APPLICATION:

SOBIL QUEN VQ is suitable for

- Cold quenching in atmosphere furnace.
- Press quenching
- Ni-Temper' or 'Triniding'.

This oil can be used for oil bath temperature upto 1000C. Water contamination in oil bath should be controlled below 200ppm.

ADVANTAGES:

SOBIL QUEN VQ Offers the following benefits:

- Marked Oxidation & Thermal stability
- Low sludge formation.
- Excellent cooling.
- Exceptional bright finish.
- Long bath life.

Guru Ram Lubricants

Kh. No. 853,874,0, Village-Dulna, Abhanpur Raipur, Chattisgarh, India. 493885 Email : gururamlubricants1042018@gmail.com Website : www.patanjalilubricants.com Mobile Number : 9302700423, 9826186101



TECHNICAL SPECIFICATIONS: SOBIL QUEN VQ

| PROPERTIES | ASTM TEST METHOD | TYPICAL VALUES |
|-------------------------------------|------------------|----------------|
| Appearance | Visual | Bright & Clear |
| Colour ASTM | D1500 | 3.0(Max) |
| Kin. Viscosity @ 100°C, cSt | D445 | 36.00 to 40.00 |
| Viscosity Index | D2270 | 95(Min) |
| Total Acid Number, Mg KOH/gm of oil | D664 | 0.5(Max) |
| Flash Point, COC, °C | D92 | 210(Min) |
| Pour Point, °C | D97 | -6(Max) |
| Moisture/Water Content, ppm | D1533 KF | 100(Max) |

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

STORAGE:

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVORNMENT, HEALTH AND SAFTEY:

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point.
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

Rev.No.00 dtd 26th Mar. 2022

Guru Ram Lubricants

Kh. No. 853,874,0, Village-Dulna, Abhanpur Raipur, Chattisgarh, India. 493885 Email : gururamlubricants1042018@gmail.com Website : www.patanjalilubricants.com Mobile Number : 9302700423, 9826186101

